

ADMISSIONS CONTROL IN A CONNECTIONLESS COMMUNICATIONS NETWORK

FIELD OF THE INVENTION

5 The present invention relates to a method and apparatus for admissions control in a connectionless communications network.

BACKGROUND TO THE INVENTION

10 Admissions control is a significant problem in communications networks and especially in connectionless, packet-based, communications networks. For example, consider a particular link in a communications network. If that link becomes congested, the traffic is unable to flow through the link and packets are dropped. This results in deterioration in quality of service for all services provided over that link. In particular
15 situations this has especially severe impact, for example, when the link provides the main access route from a communications network of a particular enterprise or residential customer to a core communications network.

These problems are particularly relevant for voice over internet protocol (VOIP) solutions. If a link is already carrying the maximum number of
20 VOIP calls, or other non-voice traffic, adding additional calls seriously degrades the voice quality of existing calls using that link. The new call added to the link also has poor voice quality. Continuing to add calls to the link degrades the quality of all calls until none of those calls are recognisable.

25 The term "Voice over Internet Protocol call" is used herein to refer calls involving any suitable type of media over internet protocol. For example, speech calls, fax calls, modem calls or video calls.

Figure 4 shows a voice over internet protocol (VOIP) communications network in which admissions control is required. A local area network 40
30 (LAN), or any suitable type as known in the art, is connected via an access link A to a core communications network 42. Any suitable type of

access link can be used as is known in the art, for example, Gigabit Ethernet, Digital Subscriber, or leased line. However, link A is unable to support calls into the core from all endpoints in the LAN simultaneously. Those endpoints are said to be "concentrated" behind link A. Concentration can be implemented in network designs for example where many of the calls are anticipated to stay on the LAN behind an access link to a core network and/or where not all of the endpoints will need to make calls into the core network at the same time. In this way a customer's LAN may be connected to a core network via a single access link that supports both voice and data at the same time. In such situations there is a need to detect when over utilisation of the access link is likely to occur in order that preventative measures can be taken. However there are currently no suitable methods for detecting link over-utilisation and communicating this to a call server or other management node in order that link over-utilisation can be prevented.

Another example is illustrated in Figure 5. In this case an enterprise network 50 is connected via a fixed wireless link 51 to a core network 52. The fixed wireless link has limited bandwidth and is unable to support calls from all endpoints in the enterprise network at one time. In addition varying amounts of bandwidth are required for calls, depending on the type of call required (e.g. voice calls can use a multitude of different codecs, each of which have their own bandwidth characteristics, fax call, etc.) and this further increases the complexity of the admissions control problem.

One known form of admissions control for the "access" portion of a network is found in the Packetcable (Trade Mark) standards for dynamic quality of service (DQOS). Packet Cable is a set of protocols developed by Cable Television Laboratories, Inc. The protocols are designed to enable quality of service enhanced communications using packetised data transmission technology to a subscriber's home over the cable network. A network superstructure that overlays the two-way data-ready digital cable television network is used. The Packetcable protocols are thus specifically designed for such cable television networks. Another disadvantage of these protocols from the point of view of admissions control is that all the internet protocol media endpoints (e.g. user terminals and other packet media endpoints) and devices on the edge of low-bandwidth links (i.e. in the Packetcable architecture, the CMTS) are

required to fully support the reservation protocol (RSVP). In addition those endpoints and devices are required to support mechanisms to send and receive session identifier information from a call server. Also the call server and the devices at the edge of the low bandwidth link need to support the common open policy service (COPS) protocol. This is problematic because many existing communications networks are formed from equipment made by different manufacturers and where many of the nodes or endpoints do not support RSVP or COPS where needed. In addition, the Packetcable protocols require all layer-3 aware devices in a media path to support RSVP in order that call admission control can be effected. However, this is not the case for many communications networks. For example, Figure 5 shows a low-bandwidth link 51 where nodes at either end of that link are only layer-2 aware devices. Therefore Packetcable protocol type call admission control mechanisms would not be effective. Other disadvantages of the Packetcable approach to call admission control include that no support for layer 2 flows is provided and the fact that all devices in the network which support RSVP are required to have some policy awareness.

The reservation protocol is defined in the Internet engineering task forces' request for comments (RFC) 2205 whilst COPS is defined in RFC 2748.

The known approach to call admissions control mentioned above which uses the Packetcable standards is now described in more detail. This approach involves the Common Open Policy Service (COPS) with RSVP. An example of a typical architecture for COPS and RSVP admissions control is given in Figure 6 which shows two access networks connected to a core communications network via Policy Enforcement Points (PEPs). The core network comprises a policy decision point (PDP) and a call server. Using this approach, the originating and terminating parties make an admissions request to the call server using H.248, or any other suitable device control protocol such as media gateway control protocol (MGCP) or NCS where NCS is the Packetcable specific version of MGCP as indicated in Figure 6. The call server then grants an appropriate service ticket to each of those parties. Next, the originating party or originating PEP spawns a network admission request through the network. A similar request is spawned by the destination party or destination PEP to request a call flow in the opposite direction and so provide a 2-way flow. The PDP receives the admission requests and forwards those to the call server.

The call server verifies the service tickets. The PDP decides whether to accept or refuse the request on the basis of available bandwidth on the low-bandwidth access link and if accepted, opens a reserved path for media for the new call. However, the COPS and RSVP approach is problematic because significant post dial delay occurs as a result of the admission process and also the other problems mentioned above with respect to the Packetcable approach apply. In addition, the means by which the call server and PDP communicate is not yet fully standardized.

More recently the Internet Engineering Task Force (IETF) have set up a working group to consider ways in which middleboxes can be controlled. The term "middlebox" is used herein to refer to an entity in a communications network which is associated with a low-bandwidth link and which is able to allow or disallow individual traffic flows over that link. For example, the middlebox may be a node connected to one end of a low-bandwidth link. Also, the middlebox may be part of a node which is not directly connected to one end of a low-bandwidth link but which is able to allow or disallow individual traffic flows over that link. The IETF working group is referred to as the MIDCOM (middlebox communications) working group. In the future it may be possible to use protocols developed by the MIDCOM working group to control such middleboxes in order that they themselves perform admissions control. However, these MIDCOM protocols are not yet developed and ratified. Indeed, we understand that the MIDCOM working group is currently working on the control of middleboxes for network address translation and firewall purposes, but not for admissions control purposes. It will be some time before this is the case and those protocols are deployed on all the required nodes in existing communications networks. In addition such MIDCOM methods would require a means by which a call server is automatically able to identify which middleboxes are relevant for a particular call. However, "middlebox discovery" mechanisms like this are not currently known.

Thus a means of providing call admission control which does not require using MIDCOM protocol methods, Packetcable protocols or COPS-RSVP approaches is required which is simple to implement, cost-effective and which is able to deal with particular situations such as conference calls, lawful intercept (known in North America as CALEA), and other potential call service situations is required.

The invention seeks to provide an improved method and apparatus for performing admissions control which solves or at least mitigates one or more of the problems mentioned above.

Further benefits and advantages of the invention will become apparent from a consideration of the following detailed description given with reference to the accompanying drawings, which specify and show preferred embodiments of the invention.

SUMMARY OF THE INVENTION

A method of providing call admission control which does not require using MIDCOM protocol methods, Packetcable protocols or COPS-RSVP approaches is described which is simple to implement, cost-effective and which is able to deal with particular situations such as conference calls and/or lawful intercept. Each link in a communications network over which it is required to perform call admissions control is provided with a middlebox connected at each end of that link such that admissions control can be carried out at one end of the link. Call services are provided by Call Servers, each of which has access to a database containing pre-specified information about all middleboxes in that call server's realm. The information in the database is manually configured for example although this is not essential. The database also has information about which media endpoints are behind what middle box, and maximum bandwidths for the link associated with each middlebox. The call servers are used to keep a running tally of the amount of VoIP call bandwidth associated with each middlebox on the edge of a low-bandwidth link, and to accept or refuse calls on the basis of the bandwidth information on a per-call basis

According to a first aspect of the present invention there is provided a call server for use in a connectionless, packet, communications network in order to provide admissions control, said communications network comprising a plurality of middleboxes, each middlebox being associated with a different link in the communications network and arranged to control packet flow over that link, said call server comprising:-

- an input arranged to receive a call admission request from an originating packet media endpoint, said call admission request

comprising information about the originating packet media endpoint, and a destination packet media endpoint;

- an input for accessing information about all first middleboxes associated with the originating node and all second middleboxes associated with the destination node, together with information about the amount of available bandwidth on the link associated with each of those middleboxes;
- a processor for determining whether to accept the call admission request on the basis of the accessed information about available bandwidth;
- an output arranged to output the results of the determination as to whether to accept the call admission request.

This provides the advantage that the call server effectively provides admission control capability on behalf of the middleboxes. Because the call server is able to access information about middleboxes and the available bandwidth on the low-bandwidth links associated with those middleboxes it is able to perform call admission control. This is achieved without the need to modify existing packet media endpoints such as media gateways and internet protocol endpoints. In addition, it is not necessary for those packet media endpoints to be fully RSVP enabled or for the middleboxes to be MIDCOM enabled with respect to call admissions control. Another advantage is that call admission control over the low-bandwidth links is achieved even where nodes at either or both ends of the low-bandwidth link are layer-2 but not layer-3 aware. This is because effectively the call server performs the admission control determinations.

The information about the destination packet media endpoint is preferably provided by a destination or called party number representing the packet media endpoint.

Preferably the processor is arranged to determine whether to accept the call admission request on the basis of the accessed information about available bandwidth together with information about the bandwidth requirements for the call. For example, a pre-specified value of the bandwidth requirements for any call can be used. Alternatively the call

server can determine what bandwidth is needed as explained in more detail below.

Preferably the processor is further arranged to determine whether all the first middleboxes are the same as all the second middleboxes and to accept the call admission request in such cases. This provides the advantage that when the call path does not traverse a low-bandwidth link associated with a middlebox then the call is simply accepted.

Advantageously said processor is further arranged to identify which of the first middleboxes are not also second middleboxes and vice versa, and wherein said processor is arranged to determine whether to accept the call admission request on the basis of accessed information about available bandwidth only for links associated with those identified middleboxes. This ensures that when the call path or flow does traverse one or more low-bandwidth links associated with middleboxes, then call admission control is performed for each of those links.

According to another aspect of the present invention there is provided a method of performing admissions control in a connectionless, packet, communications network, said communications network comprising a plurality of middleboxes, each middlebox being associated with a different link in the communications network and arranged to control packet flow over that link, said method comprising the steps of, at a call server:-

- receiving a call admission request from an originating packet media endpoint, said call admission request comprising information about the originating packet media endpoint and a destination packet media endpoint;
- accessing information about all first middleboxes associated with the originating packet media endpoint and all second middleboxes associated with the destination packet media endpoint, together with information about the amount of available bandwidth on the link associated with each of those middleboxes;
- determining whether to accept the call admission request on the basis of the accessed information about available bandwidth; and

- outputting the results of the determination as to whether to accept the call admission request.

The communications network is preferably an internet protocol communications network at layer 3. At layer 2, a variety of protocols could be used, such as ATM, Ethernet, PPP, etc. A variety of layer 1 physical layers can also be provided. The calls are preferably voice over internet protocol calls.

The middle boxes at both ends of the low-bandwidth link are arranged to use quality of service (QOS) mechanisms as known in the art to prioritise VoIP traffic from other non-VoIP traffic accessing the low-bandwidth link. This is accomplished using well known classification techniques such as packet marking, port based, VLAN based, etc., as well as traffic shaping, and traffic dropping as known in the art. The end-result is that the voice traffic always has priority over non-voice traffic. If there is ever voice traffic to be sent, it is always sent over the low-bandwidth link ahead of non-voice traffic. This results, essentially, in the voice traffic having complete access to all the available bandwidth on the access link. The term "voice traffic" is used here and in the document as a whole to refer to any suitable type of media in a voice over IP call, for example, speech, fax, video and modem.

Preferably said information about bandwidth requirements for the call comprises session description protocol (SDP) information received from both the originating and destination packet media endpoints. SDP is specified in the IETF's RFC number 2327. This provides a simple and effective means by which bandwidth requirement information can be obtained by the call server on a per-call basis. The call server is also able to adjust the bandwidth requirements used for the call if these requirements change in the SDP information, for example, as codec requirements are negotiated between the packet media endpoints during call setup time, prior to answer. (A codec is a device for converting speech into signals suitable for transfer by a packet based protocol.) Even post-answer, it is possible to use SDP changes to change the codec being used, and the call server is preferably arranged to take this into account when doing admissions control. Suppose that the call server detects a change to a new codec that requires more bandwidth than previously required for a call. In that case, if there is not enough

bandwidth on a link used in this call to change to the new codec, then the Call Server is preferably arranged to force the call to remain at the current, un-modified bandwidth.

5 In one embodiment said call is a voice call and said information about bandwidth requirements for the call comprises information about one or more codecs to be used in the call. Also, the call may be a conference call to be established using a conferencing service in the communications network. In addition the call may be subject to lawful intercept as explained in more detail below.

10 In another embodiment the communications network comprises two or more call servers, and wherein said method further comprises: receiving said call admission request at an origination call server associated with the origination packet media endpoint and determining whether a destination call server, associated with the destination packet media
15 endpoint is the same as the origination call server. This provides the advantage that admissions control for calls which traverse realms of more than one call server can be carried out.

Advantageously, when said determination indicates that the destination call server and the origination call server are different, the method
20 comprises allowing the origination and destination packet media endpoints to negotiate as to a codec to be used for the call and to send information about that codec to both the origination and destination call servers. This codec can be used to determine an indication of bandwidth requirements for the call based on the codec information. Preferably, the negotiation
25 about which codec to use is accomplished using known methods such as via session initiation protocol (SIP) or SIP-T. These protocols are able to carry SDP information regarding the call between the origination and destination call servers as described below.

30 Preferably, for all middleboxes associated with the origination packet media endpoint, the origination call server accesses information about available bandwidth and for all middleboxes associated with the destination packet media endpoint, the destination call server accesses information about available bandwidth.

Furthermore, if the call request is refused, instructions are sent to the origination packet media endpoint to provide a refusal indication to a calling party terminal which initiated the call request.

Also, if the call request is accepted, a database of middlebox information is updated with information about the call and updated again when that call ends.

Advantageously, one or more of said middleboxes are arranged to perform call admission control themselves under MIDCOM protocol control. This means that the method of the present invention can be implemented in communications networks which contain a mixture of MIDCOM enabled and non-MIDCOM enabled equipment. However the present invention does not seek to provide a MIDCOM protocol based solution although some embodiments of the present invention are operable in networks which contain a mixture of MIDCOM enabled and non-MIDCOM enabled equipment.

The invention also encompasses a communications network comprising at least one call server as specified above. Preferably, every originating and every destination packet media endpoint connected to a particular middlebox is controlled by the same call server. By specifying requirements for network topology in this way it is possible to use a simplified method of call admissions control as described herein.

The invention also encompasses a computer program arranged to control a call server such that the method specified above is carried out. Any suitable programming language may be used for the computer program as is known in the art.

The preferred features may be combined as appropriate, as would be apparent to a skilled person, and may be combined with any of the aspects of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

In order to show how the invention may be carried into effect, embodiments of the invention are now described below by way of example only and with reference to the accompanying figures in which:

Figure 1 is a flow diagram of a call admission control method according to an embodiment of the present invention;

Figure 2 is a flow diagram of another call admission control method according to another embodiment of the present invention;

5 Figure 3 is a schematic diagram of a communications network comprising a call admission control system;

Figure 4 is a schematic diagram of a prior art voice over internet protocol (VoIP) communications network;

10 Figure 5 is a schematic diagram of a prior art voice over internet protocol (VoIP) communications network;

Figure 6 is a schematic diagram of a typical COPS and RSVP admissions control architecture according to the prior art;

Figure 7 is a schematic diagram of another communications network comprising a call admission control system;

15 Figure 8 is a schematic diagram of a communications network comprising a conference bridge and a call admission control system according to an embodiment of the present invention.

Figure 9 is a schematic diagram of a communications network comprising a call admissions control system and a lawful intercept system.

20 **DETAILED DESCRIPTION OF INVENTION**

Embodiments of the present invention are described below by way of example only. These examples represent the best ways of putting the invention into practice that are currently known to the Applicant although they are not the only ways in which this could be achieved.

25 The term "low bandwidth link" is used to refer to a connection between two nodes in a communications network, where the capacity of the link is less than the capacity required should all entities connected to one end of the link issue communications over that link simultaneously. Typically there is only one such low bandwidth link between the two nodes referred to immediately above although this is not always the case.

30

The term "packet media endpoint" is used to refer to a terminal that is suitable for connection (possibly indirectly) to a middlebox or to refer to a node via which terminals access a middlebox (e.g. a media gateway).

5 The term "call agent" is used to refer to a node which is able to control a middlebox via the MIDCOM protocol. For example, a call server or a media gateway controller may be a call agent if these entities are MIDCOM enabled. In the present invention it is not essential for the call server to be MIDCOM enabled and in a preferred embodiment it is not MIDCOM enabled.

10 The present invention addresses the problem of admissions control by using a call server which has access to a pre-configured database of information about middleboxes and the available bandwidths at the low-bandwidth links associated with those middleboxes. By using pre-configured information in this way, a simple and effective means of call admission control is obtained and there is no need to make changes to existing IP media endpoints or to have MIDCOM enabled middleboxes. In addition, by specifying particular requirements for network design and topology it is possible to deal with situations in which more than one call server is involved. It is also possible to deal with complex service interactions such as conference calls and lawful intercept. In addition, the solution works for low bandwidth links where the edges of the low bandwidth link (i.e. the middle boxes) are capable of looking at either the layer 2 or layer 3 of the flow.

15 This is now explained in more detail with reference to Figures 1, 2 and 3. Figure 3 gives a schematic diagram of a communications network comprising a call admission control system according to the invention and Figures 1 and 2 are flow diagrams of methods of call admission control in the network of Figure 3.

20 Figure 3 shows a Voice over IP communications network 30 comprising a plurality of nodes interconnected by links and for clarity only some of the nodes and links are shown. The communications network 30 comprises one or more call servers and in this example two call servers 31, 32 are shown and these are interconnected by link 38, which may be indirect and which uses a suitable protocol such as SIP-T for inter-call-server communication. Each call server 31, 32 is associated with one or more middleboxes 35; that is, the call server is able to control packet media

endpoints that are behind those middleboxes with which the call server is associated. As explained above each middlebox is connected (possibly indirectly) to one or more packet media endpoints 36 and those packet media endpoints are connected to one or more terminals via which users are able to access the communications network. It is also possible for a single packet media endpoint to be connected behind more than one middlebox and thus more than one low bandwidth link although this is not shown in Figure 3 for reasons of clarity.

Considering an individual call server, this is used to provide services to terminals connected to packet media endpoints. For example, in Figure 3, call server 31 can be thought of as serving realm A and being associated with the middleboxes, packet media endpoints and terminals in its realm. Similarly call server 32 serves realm B. The two call servers 31, 32 are connected to one another either directly or indirectly. Communication between call servers 31, 32 is accomplished through the use of a well known inter-call-server communication protocol such as SIP-T as known in the art.

Accessible by each call server is a database or other information store 33, 34. These contain pre-specified information about all the middleboxes in the particular call server's realm. This information comprises:

- For each middlebox in the realm, which packet media endpoints are associated with that middlebox, as well as, for each packet media endpoint, what the associated middlebox is;
- For each middlebox in the realm the maximum possible bandwidth of the low-bandwidth link associated with that middlebox;
- For each middlebox in the realm the current available bandwidth on the associated low-bandwidth link;
- Optionally, information about whether each middlebox supports MIDCOM based protocol admissions control.

With reference to Figure 1, when a call request is made by a user of a terminal, a call request message is sent from that terminal to the associated call server via an packet media endpoint and one or more middleboxes. The call request message is preferably in the form of a device control call origination message using a protocol such as H.248,

media gateway control protocol or any other suitable protocol as known in the art.

The call request takes place in multiple stages although this is represented in Figure 1 as one stage for clarity. The stages of the call request are known in the art and the exact details depend on the particular device control protocol used. An outline of the type of steps involved is:

- Offhook from packet media endpoint to call server.
- Call server tells packet media endpoint to create connection and collect digits.
- Packet media endpoint tells call server the preferred bandwidth requirements for the call as well as IP addressing details, etc. (i.e. SDP information).
- Packet media endpoint sends digit information to the call server and the call server uses this to form the destination packet media endpoint identity.

For example, consider a call request from terminal C in Figure 1. The request message would proceed to packet media endpoint F, through middlebox 1 and to origination call server 31. The call request message contains information about the call destination as well as the origination and destination packet media endpoints (as mentioned above) and also information about the bandwidth requirements for the call (see box 10 of Figure 1).

The origination call server 31 next checks whether the origination and destination packet media endpoints are both in its realm (see box 11 of Figure 1). For example, if the destination party is terminal D in Figure 3 then this is the case; the origination packet media endpoint F and the destination node E are both in realm A. In such cases the method proceeds as in Figure 1; otherwise the method of Figure 2 is adopted.

Considering the case where the method of Figure 1 applies, the call server next checks whether call admission control is required. For example, if the origination and destination terminals are both served by the same packet media endpoint, then the call does not need to flow over a low bandwidth link and so no call admission control is needed. In order to

check this, the call server 31 accesses its middlebox database 34. Details of all first middleboxes associated with the origination packet media endpoint are found. For example, these could be middlebox 1 in Figure 3. Then details of all second middleboxes associated with the destination packet media endpoint are found. These could be middlebox 2 in Figure 3. The call server 31 then checks these two sets of middleboxes for any items which are only in one of the sets. If all of the first middleboxes are the same as the second middleboxes then no call admission is required (see boxes 12 and 13 of Figure 1) and the call request is accepted. Otherwise, any first middleboxes which are not also second middleboxes and vice versa are identified. For each of these middleboxes information about currently available bandwidth is obtained (see box 14 of Figure 1).

If the bandwidth required for the call is less than each of the available bandwidths for those middleboxes then the call is accepted (see boxes 15 and 16 of Figure 1). Otherwise the call is refused (see box 17 of Figure 1). For example, consider a call from terminal C to terminal D. The low bandwidth links associated with both middleboxes 1 and 2 have to have enough available capacity for the proposed call. (The call server may not have empirical information about the available bandwidths but instead may use a counter or token system representing units of bandwidth or any other suitable scheme for indicating the relative amount of bandwidth).

When a call is accepted, the appropriate middlebox database is updated once the call begins and when the call ends. When a call is refused it is possible for the end user to be informed, for example by sending an instruction from the call server 31 to the destination packet media endpoint to play a special tone or a recorded announcement.

When call admission is barred then it is unlikely that a centralised announcement resource can be used to play an announcement, because of congestion in the network for example. Also, in order to use a centralised announcement resource the call admission control process would need to be carried out again. In view of this a treatment tone is preferably used or an announcement resource at the packet media endpoint itself.

As described with reference to Figure 1, the call server receives information about the bandwidth requirements for the proposed call. This is preferably achieved via SDP information from the packet media

endpoints (as mentioned above). In a preferred embodiment involving VoIP calls, the call server obtains the bandwidth requirement information by examining session description protocol (SDP) messages from each of the packet media endpoints in its realm. These message enable the call server to determine which codecs will be used in the call, as is known in the art. Then, based on the codec to be used in the call, the call server is able to allocate one or more bandwidth credits to the call. A codec using more bandwidth requires more credits. Thus in this embodiment, the call server also has access to pre-specified information about all possible codecs that may be used in calls in its realm and the amount of bandwidth needed by those codecs.

The method of Figure 1 thus does not require the middleboxes to have MIDCOM capability and the packet media endpoints may be of any suitable type whether RSVP enabled or not. The method is therefore operable for networks formed from mixed equipment with some entities being MIDCOM controllable and some not if required.

In the case that the destination packet media endpoint is in a different realm from the origination packet media endpoint the method of Figure 2 is used. The origination call server 31 receives a call request from packet media endpoint E for example, where the destination packet media endpoint is G for example. The call server recognises that packet media endpoint G is not in its realm, but instead in the realm of destination call server 32. This is achieved without reference to the middlebox database. Rather, standard call server translation and routing methods are used as is known in the art to determine that access node G is in the realm of destination call server 32. The origination and destination packet media endpoints are then allowed to negotiate as to which codec will be used for the call (in the case of a VoIP call) as is known in the art. (As explained above, a codec is a device for converting speech into signals suitable for transfer by a packet-based protocol and one or more codecs are associated with each call server.) Information about which codec is to be used is then sent to each of the origination and destination call servers 31, 32 (see box 22 of Figure 2). This is preferably achieved using standard inter-call-server signalling such as SIP-T as known in the art.

Using the codec information, or other information about bandwidth requirements for the call both call servers 31, 32 allocate bandwidth

credits for the call (see box 23 of Figure 2). That is, each call server determines an indicator of how much bandwidth is needed for the call. Each call server then accesses its middlebox database to check whether the available bandwidth is enough for the call. This is done in a similar way described with respect to Figure 1. That is, each call server determines which of its middleboxes are involved in the call and checks the available bandwidth on each of the associated low-bandwidth links.

As a result, if any of the call servers decides to refuse the call, the call is refused (see box 24 of Figure 2). Otherwise, the call is accepted (see box 25 of Figure 2). If the call is refused a treatment tone or an announcement is made as described above with reference to Figure 1.

Thus the method of Figure 1 involved checking for situations where no call admission control is needed. However, the method of Figure 2 does not require such a check because the origination and destination packet media endpoints are always different when the call servers are different provided a particular network design is followed. That is, the network design should not have any middleboxes which are members of more than one realm. Such a situation is illustrated in Figure 7 which is the same as Figure 3 except that middlebox 3 is in both realms A and B.

In a preferred embodiment, the call server determines whether call admission control is required by using information from the middlebox database. For example, if the middlebox database shows that the access node concerned is behind a middlebox and also if the middlebox database shows that the call server is required to perform call admissions control on behalf of that middlebox.

However it is not essential for the call server to make this determination as described above. Another option is to add an identifier to call request messages as now described.

In order to inform the call server(s) that call admission control is required an identifier may be added to the call request message. This indicates the need for the call server to count the admissions through each middlebox on behalf of those middleboxes. However, in the case that some of the middleboxes are MIDCOM enabled and able to carry out their own call admission control, such an indicator is useful. For example, if the call

10034421 122801

server knows that a particular middlebox is MIDCOM enabled in that way, it can simply request call admission control from that middlebox.

5 In a preferred embodiment the call server uses a tag (called CAC-CSCCount for example) to note in the middlebox database each middlebox that cannot perform call admission control via MIDCOM. Using the methods of Figures 1 and 2 the call server then effectively keeps track (using a counter mechanism) of the amount of bandwidth passing the low bandwidth link connected to the middle boxes as described above. Pre-specified in the middlebox database is information about the maximum amount of bandwidth allowed through the low bandwidth link connected to each middlebox. This information is obtained in any suitable manner, for example by theoretical calculations or by empirical measurement. If the current value of the bandwidth counter would exceed the maximum amount of bandwidth specified then the proposed call is refused.

15 The method is also able to deal with situations involving conference calls where a centralised conferencing service is used. For example, consider the situation in Figure 8 which shows an access network 80 connected to a core network 81 comprising a conference bridge 83 via a low bandwidth link 82. If terminal A sets up a call to terminal C then a call path 84 is established and no admissions control is needed. However, if A proceeds to conference B into the existing call then three 2-way speech paths need to undergo admissions control, one path between each of A, B and C and the conference bridge 83. This is possible using the method of Figure 1 for each of those paths.

25 The method is also able to deal with situations involving lawful intercept whereby calls from a particular entity are intercepted for security or other lawful purposes. This is illustrated schematically in Figure 9 which is similar to Figure 8. Consider user A in Figure 9 and suppose user A to be a lawful intercept target.

30 In order for lawful intercept to proceed a centralised resource (referred to as a centralised receptor) is used in the core network. This means that all A's calls must pass the low bandwidth link, even if those calls would not otherwise need to do so (for example, calls to user B in Figure 9). As a result user A's calls to user B could be dropped as a result of call admissions procedures associated with the low bandwidth link. This could alert user A to the fact that lawful intercept is being used. In order to

35

prevent this, the present invention drops another existing call to provide enough bandwidth for A's call should this be required. In that way, A's call is not dropped and A does not have reason to become suspicious. A key requirement for lawful intercept is that lawful intercept targets are not aware that calls involving them are being monitored.

5

In Figure 3 the middlebox databases 33, 34 are shown as separate from the call servers 31, 32. However, this is not essential. The middlebox database may be integral with its associated call server, or it may be a separate entity. This is an implementation decision.

10

Any range or device value given herein may be extended or altered without losing the effect sought, as will be apparent to the skilled person for an understanding of the teachings herein.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189